

## WATER BATH / OIL BATH



ELECTRIC HEATING WATER BATH BOILER-HH-S Series



ELECTRIC HEATING  
WATER BATH-SSW Series



THREE HOLES WATER BATH  
BOILER-DK-8D

Shanghai Boxun Medical Biological Instrument Corp

Add: No. 599 Zhongqiang Road, Maogang Town,  
Songjiang District Shanghai, China

Tel: 021-56980111 Fax: 021-56303876

E-mail: export@shbxyl.com

web: www.sh-bx.com



www.sh-bx.com

## ELECTRIC HEATING WATER BATH BOILER >>

HH.S Series

### Product Feature >

- Quality steel housing with static spray plastics, stainless steel chamber;
- The temperature control system adopts high precision sensor and integrate circuit, precise and reliable;
- Diagnostic function of key electronic components.



## ELECTRIC HEATING WATER BATH >>

SSW Series

### Product Feature >

- Quality steel housing with static spray plastics, stainless steel chamber;
- The temperature control system adopts high precision sensor and integrate circuit, precise and reliable.



## THREE HOLES WATER BATH BOILER >>

DK-8D

### Product Feature >

- Stainless steel chamber and cover;
- Three holes independent temperature control;
- Timing boot and shut down, working at constant value, timing up to 99 hours;
- Sensor fault alarm, upper and lower limit temperature deviation alarm, over temperature alarm and parameter memory;
- Temperature display correction, self-diagnosis and dynamic control technology.



Model	HH.S11-1	HH.S11-2	HH.S11-4	HH.S11-6	HH.S11-8	HH.S21-4	HH.S21-6	HH.S21-8
Type	○	○○	○○○○	○○○○○○	○○○○○○○○	○○ ○○	○○○ ○○○	○○○○ ○○○○
Temp. Range [°C]	RT+5~100	RT+5~100	RT+5~100	RT+5~100	RT+5~100	RT+5~100	RT+5~100	RT+5~100
Temp. Resolution [°C]	1	1	1	1	1	1	1	1
Temp. Fluctuation [°C]	±1	±1	±1	±1	±1	±1	±1	±1
Power [W]	300	600	1000	1500	1800	800	1200	1500
Power Supply [V, Hz]	220,50	220,50	220,50	220,50	220,50	220,50	220,50	220,50
Internal Dimensions W×D×H [mm]	160×160×130	305×160×130	600×170×120	900×170×120	1200×170×120	305×305×130	470×305×130	600×290×120
Housing Dimensions W×D×H [mm]	200×200×210	345×200×210	635×205×225	935×205×225	1230×205×225	345×345×210	510×345×210	635×320×225
Opening Diameter [mm]	120	120	120	120	120	120	120	120
Net Weight/Gross Weight [kg]	2,9/3,4	4,5/5,1	7,9/9	11,2/12,6	14,3/22,4	6,2/7,3	7,8/9	10,6/12
Package Size [mm]	370*260*220	470*260*220	790*260*220	1100*260*220	1430*260*220	480*390*230	650*390*230	780*390*230

Model	SSW-420-2S	SSW-600-2S
Temp. Range [°C]	RT+5~100	RT+5~100
Temp. Resolution [°C]	1	1
Temp. Fluctuation [°C]	±0.2	±0.2
Power [W]	500	700
Power Supply [V, Hz]	220, 50	220, 50
Internal Dimensions W×D×H [mm]	420×190×150	600×300×180
Housing Dimensions W×D×H [mm]	565×220×260	745×340×295
Net Weight [kg]	8	15
Gross Weight [kg]	9	16
Package Size [mm]	670*330*340	860*450*390

Model	DK-8D
Temp. Range [°C]	RT+5~99
Temp. Resolution [°C]	0.1
Temp. Fluctuation [°C]	±0.3
Temp. Uniformity at 37°C [°C]	±0.5
Timer Range	1min~99h
Power per Chamber [W]	300X3
Power Supply [V, Hz]	220, 50
Internal Dimensions per Chamber W×D×H [mm]	150×140x120
Housing Dimensions W×D×H [mm]	620x260x240
Number of Chambers [pc]	3
Net Weight/Gross Weight [kg]	8.2/9.6
Package Size [mm]	710x325x310